

	SAFETY DATA SHEET	Page : 1 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : ANYCUBIC
ABS-Like Resin V2
UFI : WY10-YQJM-W00T-8N3P

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Use of the substance/mixture : Resin

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Shenzhen Anycubic Technology Co., Ltd
12-13th floor, Building #3B, Vanke Times Square, No.85 Longcheng Avenue, Longcheng Street
518000 Longgang District, Shenzhen, Guangdong - China
T 17688757950
weiwulin@anycubic.com

1.4. Emergency telephone number

Emergency number : 17688757950
Only available during office hours.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315
Eye Dam. 1 H318
Skin Sens. 1 H317
STOT SE 3 H335
Aquatic Chronic 2 H411

Full text of H- and EUH-statements: see section 16

	SAFETY DATA SHEET	Page : 2 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word

: Danger

Contains

: 1,2-Ethanediyil bisacrylate; (1-methyl-1,2-ethanediyil)bis[oxy(methyl-2,1-ethanediyil)] diacrylate; Oxirane, 2-methyl-, polymer with oxirane, bis(2-methyl-2-propenoate), block; phenyl bis (2,4,6-trimethylbenzoyl)-phosphine oxide

Hazard statements (CLP)

: H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER/doctor.
P391 - Collect spillage.
P405 - Store locked up.
P501 - Dispose of contents and container to an approved waste disposal plant.
Child-resistant fastening : Not applicable
Tactile warning : Not applicable

2.3. Other hazards

Other hazards

: Results of PBT and vPvB assessment : Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Oxirane, 2-methyl-, polymer with oxirane, bis(2-methyl-2-propenoate), block	(CAS-No.) 122985-55-1	30 – 40	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
1,2-Ethanediyil bisacrylate	(CAS-No.) 26570-48-9 (EC-No.) 607-960-5	10 – 25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317

	SAFETY DATA SHEET	Page : 3 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	(CAS-No.) 42978-66-5 (EC-No.) 256-032-2 (EC Index) 607-249-00-X	15 – 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411
Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-	(CAS-No.) 64401-02-1 (EC-No.) 613-584-2	10 – 20	Aquatic Chronic 2, H411
phenyl bis (2,4,6-trimethylbenzoyl)-phosphine oxide	(CAS-No.) 162881-26-7 (EC-No.) 423-340-5 (EC Index) 015-189-00-5	2 – 5	Skin Sens. 1A, H317 Aquatic Chronic 4, H413

Specific concentration limits:

Substance name	Product identifier	Specific concentration limits
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	(CAS-No.) 42978-66-5 (EC-No.) 256-032-2 (EC Index) 607-249-00-X	(10 ≤C < 100) STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance.
Inhalation	: Remove casualty to fresh air and keep warm and at rest. In case of doubt or persistent symptoms, consult always a physician.
Skin contact	: Remove contaminated clothing and shoes. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
Eyes contact	: Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
Ingestion	: Rinse mouth thoroughly with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: May cause respiratory irritation.
Skin contact	: May cause an allergic skin reaction. Causes skin irritation. The following symptoms may occur: Redness, pain.
Eyes contact	: Causes serious eye damage. The following symptoms may occur: Redness, pain. Blurred vision.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO2), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards	: Combustible. Heating will cause a rise in pressure with a risk of bursting. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Can form explosive mixture with air.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO2).

	SAFETY DATA SHEET	Page : 4 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

5.3. Advice for firefighters

Firefighting instructions	: Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
Other information	: Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel	: Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately earthed. Use explosion-proof equipment. Use only non-sparking tools.
-----------------------------	---

6.1.2. For emergency responders

For emergency responders	: Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.
--------------------------	---

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation.
-------------------------	--

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment. Contaminated work clothing must not be allowed out of the workplace. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools.
Hygiene measures	: Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

	SAFETY DATA SHEET	Page : 5 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.
Heat and ignition sources	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep out of direct sunlight.
Special rules on packaging	: Containers which are opened should be properly resealed and kept upright to prevent leakage.
Packaging materials	: Keep only in the original container.

7.3. Specific end use(s)

Resin.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information	: Recommended monitoring procedures :. Personal air monitoring. Room air monitoring
------------------------	---

8.2. Exposure controls

Engineering measure(s)	: Organisational measures to prevent/limit releases, dispersion and exposure. See Section 7 for information on safe handling. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use only outdoors or in a well-ventilated area. Take precautionary measures against static discharges. Ensure equipment is adequately earthed.
Personal protective equipment	: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hand protection	: Wear chemically resistant gloves (tested to EN374) . Suitable material: Not determined. Breakthrough time : refer to the recommendations of the supplier. Thickness : Not determined. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Use suitable eye protection (EN166): goggles. face shield
Body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: ABEK (EN 14387). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.
Environmental exposure controls	: Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Grey.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available

	SAFETY DATA SHEET	Page : 6 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

Melting / freezing point	: No data available
Freezing point	: No data available
Initial boiling point and boiling range	: 238 °C
Flash point	: 90 °C
Auto-ignition temperature	: 252 °C
Decomposition temperature	: No data available
Flammability	: Not applicable, liquid
Vapour pressure	: No data available
Vapour density	: No data available
Relative density	: No data available
Solubility	: Insoluble in water. Soluble in ethanol.
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: 1,54 m ² /s
Dynamic viscosity	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: No data available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Combustible. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

	SAFETY DATA SHEET	Page : 7 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep out of direct sunlight. See Section 7 for information on safe handling.

10.5. Incompatible materials

Strong oxidizing agents. See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate (42978-66-5)	
LD50/oral/rat	3000 - 8100 mg/kg
LD50/dermal/rabbit	> 2000 mg/kg
phenyl bis (2,4,6-trimethylbenzoyl)-phosphine oxide (162881-26-7)	
LD50/oral/rat	> 2000 mg/kg
LD50/dermal/rat	> 2000 mg/kg

Skin corrosion/irritation : Causes skin irritation.
pH: No data available

Serious eye damage/irritation : Causes serious eye damage.
pH: No data available

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

ANYCUBIC ABS-Like Resin V2	
Kinematic viscosity	1540000 mm ² /s

Other information : Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2 Other information

Other information : Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4

	SAFETY DATA SHEET	Page : 8 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate (42978-66-5)	
LC50 - Fish [1]	4,5 - 10 mg/l (Leuciscus idus)
EC50 - Crustacea [1]	88,7 mg/l (Daphnia Magna)
EC50 72h - Algae [1]	> 28 mg/l (Species: Desmodesmus subspicatus)
phenyl bis (2,4,6-trimethylbenzoyl)-phosphine oxide (162881-26-7)	
LC50 - Fish [1]	> 90 µg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])

12.2. Persistence and degradability

ANYCUBIC ABS-Like Resin V2	
Persistence and degradability	No additional information available.

12.3. Bioaccumulative potential

ANYCUBIC ABS-Like Resin V2	
Partition coefficient n-octanol/water	No data available
Bioaccumulative potential	No additional information available.

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate (42978-66-5)	
BCF - Fish [1]	(no significant bioaccumulation expected)
Partition coefficient n-octanol/water	2 (at 25 °C)

Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]- (64401-02-1)	
Partition coefficient n-octanol/water	2,45 – 4,16 (at pH 6.97)

phenyl bis (2,4,6-trimethylbenzoyl)-phosphine oxide (162881-26-7)	
Partition coefficient n-octanol/water	5,8 (at 22 °C (at pH 8.3)

12.4. Mobility in soil

ANYCUBIC ABS-Like Resin V2	
Mobility in soil	No data available

	SAFETY DATA SHEET	Page : 9 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

12.5. Results of PBT and vPvB assessment

ANYCUBIC ABS-Like Resin V2	
Results of PBT assessment	Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects : No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Packaging contaminated by the product : Do not pierce or burn, even after use. Never use pressure to empty container.

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC) : This material and its container must be disposed of as hazardous waste
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
3082	3082	3082	3082	3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-])	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-])	Environmentally hazardous substance, liquid, n.o.s. ((1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-])	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-])	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-])
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((1-methyl-1,2-	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((1-methyl-1,2-	UN 3082 Environmentally hazardous substance, liquid, n.o.s. ((1-methyl-1,2-	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((1-methyl-1,2-	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((1-methyl-1,2-

	SAFETY DATA SHEET	Page : 10 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

ADR	IMDG	IATA	ADN	RID
ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-], 9, III, (-)	ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-], 9, III, MARINE POLLUTANT	-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-], 9, III	ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-], 9, III	ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-], 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) : M6
Special provisions : 274, 335, 375, 601
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13
Hazard identification number (Kemler No.) : 90

	SAFETY DATA SHEET	Page : 11 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

Orange plates : 

Tunnel restriction code : -
EAC code : •3Z

- Transport by sea

Special provisions (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A97, A158, A197, A215
ERG code (IATA) : 9L

- Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19

	SAFETY DATA SHEET	Page : 12 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

Portable tank and bulk container instructions (RID) : T4

Portable tank and bulk container special provisions (RID) : TP1, TP29

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31

Colis express (express parcels) (RID) : CE8

Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Listed on REACH Annex XVII (Restriction Conditions). The following restrictions are applicable:

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	ANYCUBIC ABS-Like Resin V2 ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Oxirane, 2-methyl-, polymer with oxirane, bis(2-methyl-2-propenoate), block
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	ANYCUBIC ABS-Like Resin V2 ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ; Poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(1-methylethylidene)di-4,1-phenylene]bis[.omega.-[(1-oxo-2-propen-1-yl)oxy]-

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

15.1.2. National regulations

France

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4511.text	Dangereux pour l'environnement aquatique de catégorie chronique 2.		
4511.1	La quantité totale susceptible d'être présente dans l'installation étant : 1. Supérieure ou égale à 200 t Quantité seuil bas au sens de l'article R. 511-10 : 200 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	A	1
4511.2	La quantité totale susceptible d'être présente dans l'installation étant : 2. Supérieure ou égale à 100 t mais inférieure à 200 t Quantité seuil bas au sens de l'article R. 511-10 : 200 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	DC	

Germany

	SAFETY DATA SHEET	Page : 13 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

Regulatory reference : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

German storage class (LGK) : LGK 10 - Combustible liquids

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Hazardous Incident Ordinance (12. BImSchV) : Listed in the 12. BImSchV (Annex I) under: 1.3.2
Quantity threshold for operational area under § 1 para. 1

- Sentence 1: 200000 kg
- Sentence 2: 500000 kg

Netherlands

Waterbezwaarlijkheid : A (2) - Vergiftig voor in water levende organismen
kan in het aquatische milieu op lange termijn schadelijke effecten veroorzaken

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class III-1

Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

Not applicable

SECTION 16: Other information

Abbreviations and acronyms:

	ABM = Algemene beoordelingsmethodiek
	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
	ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
	CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods Code
	LEL = Lower Explosive Limit/Lower Explosion Limit
	UEL = Upper Explosion Limit/Upper Explosive Limit
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	BTT = Breakthrough time (maximum wearing time)
	DMEL = Derived Minimal Effect level
	DNEL = Derived No Effect Level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate

	SAFETY DATA SHEET	Page : 14 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

	EWC = European waste catalogue
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	NA = Not applicable
	NOEC = No observed effect concentration
	NOEL: no-observed-effect level
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	N.O.S. = Not Otherwise Specified
	OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	PNEC = Predicted No Effect Concentration
	Quantitative structure-activity relationship (QSAR)
	STOT = Specific Target Organ Toxicity
	TWA = time weighted average
	VOC = Volatile organic compounds
	WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the datasheet : ECHA (European Chemicals Agency). LOLI. Supplier information.

Training advice : Training staff on good practice. Manipulations are to be done only by qualified and authorised persons.

Other information : Classification - Assessment method: CLP Calculation method (Article 9). Physicochemical hazard assessment: Information given is based on tests on the mixture itself.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is

	SAFETY DATA SHEET	Page : 15 / 15
		Revision nr : 1.0
		Issue date : 15/05/2023
	ANYCUBIC ABS-Like Resin V2	Supersedes :

provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

ANYCUBIC